

LED LOW GLARE BATTEN



4000K
CCT



>60,000hrs
@ L80



>93
CRI



5 Year
Warranty



UGR<19

- ✓ Compliant with MoE (Ministry of Education) specification
- ✓ Multi Wattage Driver
- ✓ Low glare diffuser for excellent visual comfort
- ✓ CRI>90 & R9>50 for excellent colour rendering
- ✓ High system efficacy of up to 120lm/W
- ✓ Flicker Free
- ✓ Wide 90° beam angle for improved uniformity
- ✓ Dimmable options include DALI-2 and Casambi control



CODE	DEFAULT POWER	DEFAULT LUMEN OUTPUT	EFFICACY	DIMENSIONS	WEIGHT
FOCUS5FT-40-940	40W	4,800lm	120lm/W	1500x124x64mm	3.45kg
FOCUS4FT-30-940	30W	3,600lm	120lm/W	1200x124x64mm	2.94kg

See page two for all wattages and outputs

LIGHTING DATA

Light Source	SMD LED
Lifetime @L80 B10	>60,000hrs
CCT	4000K
CRI	>90
R9 Value	>50
SDCM	<3
UGR Rating	19*
Beam Angle	90°

DESIGN / CONSTRUCTION

Body Material	Steel
Diffuser Material	PMMA
Finish	Powder-Coated
Colour	White
Installation	Surface mounted, Suspension wire

ELECTRICAL DATA

Driver Brand	Boke
Mains Voltage	AC220-240V / 50-60 Hz
Power Factor	>0.95
THD	<10%
Driver Lifetime	>50,000hrs
Flicker Free	Yes (PstLM <1 / SVM <0.4)
Dimming Options	DALI (suffix: -DA) SwitchDim (suffix: -SD)

TECHNICAL DATA

IP Rating	IP40
Operating Temp	-20° to +40°C
Protection Class	Class 1
Certifications	SAA
Warranty	5 Year product replacement

ACCESSORY CODES

Codes	Variant Description
EXCELSUS	Suspension Kit

* See UGR chart on page two for more information