ACE SURFACE

LOW GLARE DOWNLIGHT

EVOLVE LIGHTING

3000K / 4000K	>90	UGR <19	50°	Triac	5 Year
SWITCHABLE CCT	CRI	LOW GLARE	BEAM ANGLE	DIMMABLE	WARRANTY

- ✓ Switchable CCT — 3000K / 4000K from one fixture
- ✓ CRI >90 high-fidelity colour rendering
- ✓ Low glare optic — UGR <19
- ✓ Flicker free (PstLM <1 / SVM ≤0.4)
- ✓ Triac (phase-cut) dimmable
- ✓ 8W / 10W output options
- ✓ Quick-connect terminal wiring
- ✓ 5 Year product replacement warranty



CODE	FINISH	POWER	LUMEN OUTPUT	BEAM	BODY SIZE
ACES90-10-934-W	White (RAL9016)	8W / 10W	800–1030lm	50°	Ø90 × 94mm
ACES90-10-934-B	Black (RAL9005)	8W / 10W	800–1030lm	50°	Ø90 × 94mm

LIGHTING DATA

Light source	SMD LED
CCT	3000K / 4000K, switchable
CRI	>90
SDCM	<3
Lumen output	800–1030lm
Efficacy	up to 100lm/W
Beam angle	50°
Glare Rating	UGR <19

ELECTRICAL DATA

Mains voltage	AC220–240V / 50Hz
Power factor (typ)	>0.85
Driver	Isolated
Dimming	Triac (phase cut)
Flicker	Flicker free, PstLM <1 / SVM ≤0.4
Connection	Quick-connect terminals
Protection class	Class II

TECHNICAL DATA

Mounting	Surface-mounted (ceiling)
Body size	Ø90 × H94mm
Operating temp	-20° to +40°C
Aperture	Ø82mm
Warranty	5 year product replacement

DESIGN / CONSTRUCTION

Housing	Plastic-coated aluminium body
Optics	PC lens
Colours	White (RAL9016) / Black (RAL9005)
Mounting	Surface-mounted


P 0800 357 6311 E sales@evolve-lighting.co.nz

ACE SURFACE

LOW GLARE DOWNLIGHT


EVOLVE LIGHTING

DIMENSIONS



Ø90MM BODY · Ø82MM APERTURE · 94MM HEIGHT · SURFACE-MOUNTED · ALL DIMENSIONS IN MM

PHOTOMETRIC DISTRIBUTION



POLAR INTENSITY (CD) · C0/180 AND C90/270 PLANES · AVERAGE BEAM ANGLE (50%): 48.8°

FINISHES



WHITE (RAL9016) · **ACES90-10-934-W**



BLACK (RAL9005) · **ACES90-10-934-B**

P 0800 357 6311 E sales@evolve-lighting.co.nz